Command Line parameters in MultiPing

Saved From: https://www.pingman.com/kb/article/command-line-parameters-in-multiping-58.html

Question

Does MultiPing have any options to start pinging targets from the command line?

Solution

MultiPing does have a few options that can be used on the command line:

Loading a workspace.

You can load a workspace file from the command line by specifying that on the command line. Note that it must have a .mws extension to be recognized by a MultiPing workspace.

Example:
multiping.exe myworkspace.mws

Pinging targets at startup.

To ping targets, pass those targets on the command, one or more:
multiping.exe www.mytarget1.com www.mytarget2.com

Start Pinging on startup

Use the /START command line parameter to start pinging on load. Example:

multiping.com www.mytarget1.com /start

Use a different configuration file

You might want to load a different combination of settings for one or more instance of MultiPing. To override this settings, user the /INIFILE: parameter. Example:
multiping.com /INIFILE:MyNewFile.ini

Note: The default MultiPing install will allow you to automatically load a workspace file and start pinging without having to use any command line parameters. Just turn on the option 'Auto Save/Load Default Workspace' in the 'Edit' menu. Also, turn on 'Auto-Start Pinging when a new target is added' in the Edit->Options, Display dialog.

This knowledgebase article and content copyright by Pingman Tools, LLC